



OTANI®

AGRICULTURAL RADIAL CATALOG 2018



05/2018



A-10

RIM DIAMETER	TIRE SIZE	LI/SS	PATTERN	TYPE	RIM WIDTH		SECTION WIDTH	OVERALL DIAMETER	RC	SLR	SRI	INFLATION MAXIMUM LOAD						
					REC inch	ALT inch						mm	mm	mm	mm	mm	mm	mm
					kgf/cm ² km/h	0.6	0.8	1	1.2	1.4	1.6							
24"	320/85 R 24 (12.4 R 24)	122 A8	A-10	TL	W10	W9, W10	305	1142	3465	515	550	50	715	840	980	1105	1230	1360
		122 A8	A-10	TL	W10	W9, W10	305	1142	3465	515	550	40	825	960	1095	1230	1365	1500
		122 A8	A-10	TL	W10	W9, W10	305	1142	3465	515	550	30	885	1030	1175	1320	1460	1605
		122 A8	A-10	TL	W10	W9, W10	305	1142	3465	515	550	10	1110	1290	1470	1650	1830	2010
30"	420/85 R 30 (16.9 R 30)	140 A8	A-10	TL	W15L	W13, W14L	405	1459	4455	660	700	50	1215	1440	1640	1830	2070	2300
		140 A8	A-10	TL	W15L	W13, W14L	405	1459	4455	660	700	40	1375	1600	1825	2050	2275	2500
		140 A8	A-10	TL	W15L	W13, W14L	405	1459	4455	660	700	30	1475	1715	1955	2195	2435	2675
		140 A8	A-10	TL	W15L	W13, W14L	405	1459	4455	660	700	10	1845	2145	2450	2750	3050	3350
	460/85 R 30 (18.4 R 30)	145 A8	A-10	TL	W16L	W14L, W15L	487	1564	4686	694	725	50	1440	1550	1900	2100	2400	2650
		145 A8	A-10	TL	W16L	W14L, W15L	487	1564	4686	694	725	40	1595	1860	2120	2380	2640	2900
		145 A8	A-10	TL	W16L	W14L, W15L	487	1564	4686	694	725	30	1710	1990	2270	2550	2830	3150
		145 A8	A-10	TL	W16L	W14L, W15L	487	1564	4686	694	725	10	2140	2490	2840	3190	3540	3890

